



**TECHNICAL DATA
MODEL JX750SSF
BJM Pumps® SUBMERSIBLE PUMP - 316 SS
For High Temperature Service
GENERAL DATA**

MAX. FLOW: GPM (L/min)	91 GPM (344 L/min)
MAX. HEAD: ft (m)	50' (15.2 m)
MAX. SUBMERSION DEPTH: ft (m)	65' (20m) or limited to length of power cord, Consult factory for deeper depths
PUMP TYPE	SUMP, HIGH TEMPERATURE
SOLID SIZE: in (mm)	3/16" (4.7 mm)
STRAINER OPENING	0.5625"x0.25" (14.3x6.3 mm) slot
IMPELLER DIAMETER: in (mm)	4.33" (110 mm)
DISCHARGE SIZE	2" NPT-MALE
PUMP WEIGHT, without cable: lbs (kg)	55 lbs (25 kg)
SHIPPING WEIGHT: lbs (kg)	70 lbs (31.8 kg)

CONSTRUCTION / MATERIAL DATA

MECHANICAL SEAL - UPPER	CARBON/ SILICON CARBIDE, FKM
MECHANICAL SEAL - LOWER	SILICON CARBIDE/SILICON CARBIDE, FKM
MOTOR CASING	316 SS
PUMP VOLUTE	316 SS
IMPELLER- MULTI VANE	316 SS
STRAINER	316 SS
LIPSEAL & O-RINGS	FKM
ROTOR SHAFT	316 SS
EXTERNAL HARDWARE	316 SS
QTY. OIL IN MOTOR STATOR	OIL-FILLED W/ SHELL FM 32, NSF APPROVED
QTY. OIL IN SEAL CHAMBER	10.1 U.S. FL. OZ. (300 C.C.), SHELL FM 32, NSF APPROVED
BALL BEARING: OIL LUBRICATED UPPER	6203
BALL BEARING: OIL LUBRICATED LOWER	6304

ELECTRICAL / MOTOR DATA

MOTOR: TYPE, RATING HP	Submersible, Oil-Filled , Continuous Duty, 1	
MOTOR RPM	3450	
MOTOR INSULATION CLASS	R, 428°F (220°C)	
MOTOR SERVICE FACTOR	1.1	
VOLTAGE - 1 PH, 60 Hz	115V	230V
CURRENT F.L.A.	16	8.5
LOCKED ROTOR CURRENT (LRA)	70	35
POWER CORD: GAGE; LENGTH	A.W.G. 14/4; 50' (15.2 m), High temp. rated cord	A.W.G. 16/4; 50' (15.2 m), High temp. rated cord
SENSOR CORD ¹ : GAGE; LENGTH	A.W.G. 18/4; 50' (15.2 m), HIGH TEMP. RATED CORD	
START COMPONENTS	CAPACITOR & START RELAY COMPONENTS ARE IN CONTROL PANEL	
MOTOR PROTECTION	THERMAL SENSOR SWITCHES EMBEDDED IN EACH WINDING, 300°F (149°C)	
MAXIMUM LIQUID TEMPERATURE	200°F (93°C)	
SEAL LEAK DETECTOR	Seal Minder®; MOISTURE SENSING PROBE	

1- Seal Minder® & thermal sensor cable must be properly connected to a control panel to maintain warranty.

©2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

104 John W Murphy Drive
New Haven, CT 0613, USA

Tel: (860) 631-3618 - Fax: (860) 399-7784

REFER TO REVERSE SIDE FOR PUMP PERFORMANCE CURVES SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Seal Minder® is a registered trademark of Industrial Flow Solutions Operating, LLC. All rights reserved.

© 2020 Industrial Flow Solutions Operating, LLC. All rights reserved.

MODEL: JX750SS-F

